

# Tumble dryer

## T5190

### Features and benefits

- **Compass Pro<sup>®</sup> microprocessor offers:**
  - Large display and one control knob for easy program selection
  - Language selection
  - Quick selection and option buttons for the most frequently used drying programs and options
  - Drying program packages optimized for Economy, Care and Time and option buttons for selection of dryness
  - Service program for adjustment of parameters
  - USB connection
- High productivity - 2 full loads per hour
- Low energy consumption for optimal efficiency
- Reversible door hanging for a convenient laundry flow
- Easy access to vital parts from front and rear for simple servicing
- The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption
- Residual Moisture Control for an accurate drying result and a low energy consumption
- Reversing drum for less tangling of large items

### Main options

- Stainless steel front
- Stainless steel drum
- Payment: coinmeter with Ecopower, chipcard reader, CP connection
- Stainless steel base frame
- Separate condense system
- Fresh air intake



Images shown are a representation of the product only and variations may occur.

Main specifications			T5190			
Rated capacity, filling factor 1:18		kg/lb	10.6/23			
	filling factor 1:22	kg/lb	8.6/19			
Drum volume		litre	190			
Drum diameter		mm	680			
Heating,	electric	kW	6/8			
	gas	BTU/h (kW)	20500/27300 (6/8)			
<b>Consumption data*</b>			6 kW	8 kW	Gas 6 kW	Gas 8 kW
Total time full load		min	35	27	36	29
Energy consumption full load		kWh	3.45	3.53	3.67	3.74
Evaporation		g/min	102	129	106	131
Energy kWh/litre water evaporated		kWh/l	0.92	0.94	-	-

\* At rated capacity 100% cotton load at 50% initial moisture dried to 0%.

Electrical connections*					
Heating alternative	Main voltage		Heating power kW	Total power kW	Recommended fuse A
		Hz			
Electric heated	220-240V 1 -	50/60	6.0/8.0	6.3/8.3	35/50
	220-230V 3 -	50/60	6.0/8.0	6.3/8.3	20/25
	240V 3 -	50/60	6.0/8.0	6.3/8.3	16/25
	380-415V 3 -	50/60	6.0/8.0	6.3/8.3	10/16
	440/480V 3 -	60	6.0/8.0	6.3/8.3	10/16
Gas heated	220-480V 1/3 -	50/60	-	0.3	10

Gas and air connections			T5190
Gas		ISO 7/1-R	1/2"
Gas pressure	Natural gas	Pa	2000
		mbar	20
	Propane	Pa	2800-5000
		mbar	30
Air outlet		ø mm	125
Evacuated air	6 kW	m <sup>3</sup> /h	270
	8 kW		290
Pressure drop	6 kW	Max. Pa	380
	8 kW		350

### Sound levels

Airborne sound level		dB(A)	68
----------------------	--	-------	----

### Heat emission

% of installed power, max			15
---------------------------	--	--	----

### Shipping data\*\*

Weight		net, kg	99
Shipping volume		m <sup>3</sup>	0.83

### Dimensions in mm

A	Width	721
B(a)	Depth (Gas)	778
B(b)	Depth (El)	759
B(c)	Depth	684
C	Height	1114
D		404
E		45
F		180
G		88
H		113
I		79
J		561

- 1 Operating panel
- 2 Door opening ø 400 mm
- 3 Electrical connection
- 4 Gas connection
- 5 Exhaust connection

\* Other voltages available, see installation manual.

\*\* Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

